

POLSKA / Poland

2Press sp. z o.o.

Plac Niepodległości 28, 64-300 Nowy Tomyśl NIP: 788-203-07-67, REGION: 385417374

ČESKO / Czech Republic

2PRESS HOLDING s.r.o. Ježkova 1054/10, Praha 3 13000 DIC CZ06288961, IČO 06288961

KAYM 48 PD PAPER CUTTER







Basic information

Name: KAYM 48 PD PAPER CUTTER

Producer: KAYM Year: 2022

Reference number: KAYM 48 PD PAPER CUTTER

Opis Dodatkowy

GENERAL TECHNICAL SPECIFICATIONS: Digital Coordinate Measurement and Indicators (Display Screen)

50 programs x 50 program steps 2.500 pcs. program position memory Program Numeric Control Manual and Semi-Automatic Operation Modes Equal (endless) Division-Program Backgauge controll by program Automatic backgauge orientation by forward-rearward btuttons Sensitive positioning of backgauge by hand-knob Chrome Table (stainless surface) Table Light Cutting Light Line function Three-phase (380V / 50Hz) Electrical System Lockable Main Switch Linear Guide Precission-Ball Screw Hydraulic Clamping, min-max. pressure adjustment Gradual Pressure by foot pedal Eccentric-Driven Cutting System Double-Hand Button Security System Light Barrier Security Protection (Photocells) The Backgauge Angulation and Skewness Removal System

Stan techniczny maszyny

Brand new

Serwis

We provide professional service of printing machines. Thanks to the in-depth knowledge of the printing industry with which we have been associated for over 20 years, we can offer comprehensive maintenance services.

Technical data

KAYM 48 PD 480 mm Cutting width Feeding depth 480 mm Feeding height max. (without false plate) 65 mm Front table length (D) 332 mm Table Height 900 mm Min. & max. clamp pressure 75/800 daN Knife speed (by direct command) 40 tur / min. Knife grinding reserve max. 15 mm Smallest cut without false plate, manual 15 mm

Smallest cut with false plate, automatically

Power Supply (220/380) 1,5 Kw

Backgauge Power Supply 0,09 Kw

Knife Dimensions (length x width x thickness) 600 x 60 x 8 mm

Machine dimensions

KAYM 48 PD Width with side tables (B) 920 mm Depth (A) 1.110 mm Depth frame (C) 450 mm Height frame (E) 1.155 mm Total weight (brut) 375 kg

Additional options

KAYM 48 PD

Monofaze (220V / 50Hz) Elektrik Sistemi

Optional